

NORTH AYRSHIRE COUNCIL DEVELOPMENT PLANNING SERVICES

SPECIFICATIONS TO DEVELOPERS FOR STREET NAMEPLATE SIGNS

Wall Mounted Street Nameplate

Non-reflective, helvetica medium lettering, black on white background on 3mm aluminium plate, rounded corners and 8mm black border. Sealed with appropriate weatherproof clear protective material. Lettering to be 75mm, upper case, and on two or more lines if appropriate.

Mounted on timber backing plate, 12mm thick, painted and weatherproofed as appropriate, overall size 10mm larger than sign, all secured by 8 steel hardened, galvanised screws, with white caps, and rawlplugs.

Free Standing Street Nameplates with Poles

Same specifications as wall mounted nameplate (excluding timber backing plate etc) but with riveted channel rails and 4 x 76mm stainless steel anti-rotational clips, plus 2 x 76mm diameter, 105m grey PVC material coated poles, bitumen coated internal surfaces, galvanised base plates, plastic pole caps, to allow mounting height of 1 metre and foundation depth of 500mm.

Fitted in 300mm x 300mm x 500mm deep hole, ancillary concrete mix ST2 or similar approved mix, concrete foundations to be float finished flush with existing hard surfaces, and painted with bitumen paint to match. Soft soil, verge, turf etc. to be reinstated to original surface, where appropriate on top of concrete foundation.

Contractors must secure all necessary road opening permits required for groundworks involved in erection of pole mounted street signs and must also satisfy themselves as to the position of all services, under or in proximity to these groundworks, and take any measures required to safeguard such services, and safety of their operatives.

Position of Street Nameplates

Types and positions of nameplates to be decided by Development Planning Services and Developer to take appropriate instructions.